Choose a product.
Build a clear buying brief.

Reference formats for distributors and interior project buyers. Use this brief to shortlist a product, then confirm its complete configuration with LISI Decor.

01 SPC flooring

View the SPC flooring collection - classic planks, EIR textures, patterned layouts and stone-look formats.

Collection / model reference	Nominal format (mm)	Base (mm)	Wear layer (mil)
Wanjia **M-2** - Winter Warmth	1220 x 180	5 / 6	12 / 20
Tiangong EIR **TB-8001** - Wheaten Sand	1520 x 225	6	12 / 20
Diequ Herringbone **R-8001** - Leisure Courtyard	640 x 128	6	12 / 20
Diequ Chevron **YG-601** - Geisha	1220 x 300	6	12 / 20
Qiyan Stone & Rock **W-6501** - Stone Light Snow	800 x 400	5.5	12 / 20

Thickness matters. SPC base thickness excludes optional 1-2 mm IXPE backing. Confirm finished thickness, wear layer, backing, locking system and the chosen format in your quotation. Catalogue options do not confirm every possible combination.

02 Indoor WPC flooring

Yulan collection - wood-inspired finishes for indoor flooring applications.

Format	Base thickness	IXPE backing	Finished thickness
1520 x 225 mm	8 / 10 mm	2 mm standard	10 / 12 mm

Wear layer: 20 mil. Compare available finishes using a physical sample. This is an indoor WPC flooring range; do not specify it as outdoor decking.

Before selecting: describe the room, expected use, site conditions and destination. Confirm suitability and the selected configuration before ordering.

Match the wall system to the intended application.

SPC, PVC and WPC are product families. Compare the dimensions and construction of the selected system rather than relying on the material name alone.

03 Wall panel systems and profiles

System	Catalogue dimensions (mm)	Construction / selection note
R-SPC	400 x 800 or 600 x 1200 5 mm thickness	Solid homogeneous SPC core.
L-SPC	400 x 800 or 600 x 1200 8 mm thickness	ABA: rigid SPC outer layers with a foamed wood-plastic middle.
F-SPC	1238 x 3000 2.5 mm thickness	Flexible core with decorative finish. Confirm curvature and installation requirements.
PVC flat panel	1220 x 2440 6.8 mm thickness	Charcoal fine-cell core with decorative PVC film. Confirm substrate and adhesive compatibility.
Small PVC fluted profile	150 x 10 x 3000 (W x T x L)	Decorative profile; confirm the selected finish and profile combination.
Large PVC concave profile	60 x 13 x 3000 (W x T x L)	Decorative profile; confirm the selected finish and profile combination.
WPC wall panel	1220 x 2440 8 mm thickness	Cream fine-cell WPC with decorative film. Confirm colour and texture using a physical sample.

Dimensions are catalogue references, not an installation specification. Confirm the selected finish, substrate preparation, installation method and any application-specific requirements before approval.

04 Include these details in your inquiry

Product and finish - Category, system or model code, colour and preferred format.

Quantity and destination - Estimated order quantity, its unit and destination country or port.

Application and configuration - Indoor setting, site conditions, thickness, wear layer, backing and installation requirements.

Samples, documents and order needs - Sample references, required documents, packaging preferences and requested timing. Confirm availability and scope for the selected configuration.

Ready to discuss a selection? Prepare your buying brief or check which sample to request. For further reading: flooring comparison or wall panel comparison.